Riverside Yacht Club Junior Sailing

Feva Safety Checklist



Skipper Name:	DOB:
Crew Name:	DOB:
Combined Crew Weight:	RYC Sticker #:
Sail #:	

JSA Roster Registration – If participating in JSA regattas.

Life jacket – USCG-approved Type III PFD; properly sized; labeled.

Whistle – Functional and attached to life jacket by lanyard long enough for use.

Class Equipment – The Skipper represents that he or she has not made any addition or alteration to the hull form, construction, equipment, type of equipment, placing of equipment, fittings, type of fittings, placing of fittings, spars, standing rigging, sails, battens and running rigging as supplied by a Builder except as allowed by the Class Rules.

Bow line – 28 ft: 3/8 inch in diameter; buoyant; loop in the end of the line; run through the forward most hole of the jib tack fitting; tied to the mast.

Daggerboard – Securely attached to the boat with a line or shock cord attached to the small hole in the upper forward corner of the daggerboard and the bow eye; labeled.

Rudder System - Properly functioning rudder catch; universal free of wear; labeled.

Forestay – Short enough to hold the front edge of the mast forward of the aft face of the mast partner when the jib halyard is released.

Sails – Mainsail, jib and spinnaker were manufactured by the official Class Sailmaker and have the official Class patch.